

60MEA2100-Signal Generator is a very convenient tool for MEA-System users. Use the 60MEA2100-SG instead of setting up a complete experiment for training, controlling, and troubleshooting purposes.

Important: When using a 60MEA2100-SG within the MEA2100-60- or the MEA2100-2x60-System, the contact padto the internal reference is disconnected. Otherwise the delivered signals are not acceptable.Please insert the 60MEA2100-SG in correct orientation as shown on the picture.

Switch on: Press control button. Switch off: Press control button longer than two seconds.

The position of DIP switch 1 and DIP switch 2 define the catagory of the signal, sine waves or real signals in digitized form. To change signals within one category, press the control button so many times (n) - one press slowly after the other - which are needed to create the desired signal of that category.

Please consider the different levels of amplitudes in electrode displays in direct vicinity regarding to the contact pads of 60MEA2100-SG, but not to the electrode displays. The amplitude alternates in a range of 100 % and 50 %. If there is a short circuit between neighbor pads of contact pads, all electrodes will show the same averaged amplitude. For more information, please read the MEA-Signal Generator Manual.

Table: DIP switch position, number of control button presses and corresponding signals

	Switch 1	Switch 2	2 Control button presses n times	Signal	
	OFF	OFF	→ 1 = MEA-SG ON	Sinus	0.005 Hz
			2	Sinus	0.01 Hz
			3	Sinus	0.03 Hz
			4	Sinus Sinus	1.25 Hz 12.5 Hz
				51105	
	ON	OFF	→ 1 = MEA-SG ON	EPSP	
			2	Populatic	on Spike
			3	Spikes	
	OFF	ON	→ 1 = MEA-SG ON	ECG Atri	um
			2	ECG Ven	tricle
			3	Ventricle	FP
	ON	ON	1 = MEA-SG ON	ERG with	n Spikes
ulti Channel Systems CS GmbH			hone +49-7121-909 25- 0 ax +49-7121-909 25-11	© 2019 Multi Channel Systems MCS Gmbl a division of Harvard Bioscience, Inc.	
spenhaustrasse 21 2770 Reutlingen		Sä	ales@multichannelsystems.com	Product information is subject to change	

www.multichannelsystems.com

Germany

Product information is subject to change without notice.





60MEA2100-SG

60MEA-Signal Generator for MEA2100-(2x)60-Systems

Switch 1	Switch 2	Press Button slowly n times	Signal Source	Signal Type
OFF	OFF	1 The MEA-SG is on	Artifical sine waves (1.75 mV) 0.005 Hz Note: Sine waves < 1 Hz might not be visible because of the hardware filter bandwidth.	\mathcal{M}
		2	Sine wave 0.01 Hz	
		3	Sine wave 0.03 Hz	
		4	Sine wave 1.23 Hz	
		5	Sine wave 12.5 Hz	
ON	OFF	1 The MEA-SG is on	Hippocampal slice EPSP	
		2	Hippocampal slice Population spikes	1
		3	Hippocampal neurons Spikes	
OFF	ON	1 The MEA-SG is on	Heart ECG Atrium	
		2	Heart ECG Ventricle	-1-1-
		3	Cardiomyocytes Vetricle FP	-+v+v
ON	ON	1 The MEA-SG is on	Retina ERG with spike	

Multi Channel Systems MCS GmbH Aspenhaustrasse 21 72770 Reutlingen Germany

+49-7121-909 25- 0 Phone +49-7121-909 25-11 Fax

© 2019 Multi Channel Systems MCS GmbH a division of Harvard Bioscience, Inc.

sales@multichannelsystems.com www.multichannelsystems.com

Product information is subject to change without notice.