





## Technical Specifications: MEA-IT-System

General Specification         Operating Temperature       10 °C to 50 °C         Storage Temperature       0° C to 70 °C         Operation Humidity       10 - 85 %, non condensing         Storage Humidity       10 - 85 %, non condensing         Storage Humidity       10 - 85 %, non condensing         MEA-IT Device       To 250 mm x 140 mm x 25 mm         Dimensions (W x D x H)       250 mm x 140 mm x 25 mm         Weight       1100 g         Number of Channels       60, 120 or 256 channels         Measurement range       5 kOhm to 2 MOhm         Test Signal       100 mV, 1 kHz Sinus         Accuracy       5 %         Power Supply       USB powered         Power supply       USB powered         PC interface       USB 2.0         Software       Version 1.5 and higher		
Storage Temperature0° C to 70 °COperation Humidity10 - 85 %, non condensingStorage Humidity10 - 85 %, non condensingMEA-IT DeviceDimensions (W x D x H)250 mm x 140 mm x 25 mmWeight1100 gNumber of Channels60, 120 or 256 channelsMeasurement range5 k Ohm to 2 MOhmTest signal100 mV, 1 kHz SinusAccuracy5 %Power SupplyUSB poweredPower supplyUSB poweredPC interfaceUSB 2.0	General Specification	
Operation Humidity10 - 85 %, non condensingStorage Humidity10 - 85 %, non condensingMEA-IT DeviceDimensions (W x D x H)250 mm x 140 mm x 25 mmWeight100 gNumber of Channels60, 120 or 256 channelsMeasurement range5 kOhm to 2 MOhmTest signal100 mV, 1 kHz SinusAccuracy5 %Power SupplyUSB poweredPower supplyUSB poweredPC interfaceUSB 2.0	Operating Temperature	10 °C to 50 °C
Storage Humidity       10 - 85 %, non condensing         MEA-IT Device       250 mm x 140 mm x 25 mm         Dimensions (W x D x H)       250 mm x 140 mm x 25 mm         Weight       1100 g         Number of Channels       60, 120 or 256 channels         Measurement range       5 kOhm to 2 MOhm         Test Signal       100 mV, 1 kHz Sinus         Accuracy       5 %         Power Supply       USB powered         PC interface       USB 2.0	Storage Temperature	0° C to 70 °C
MEA-IT Device       Dimensions (W x D x H)     250 mm x 140 mm x 25 mm       Weight     100 g       Number of Channels     60, 120 or 256 channels       Measurement range     5 kOhm to 2 MOhm       Test Signals     100 mV, 1 kHz Sinus       Accuracy     5 %       Power Supply     USB powered       PC interface     USB 2.0	Operation Humidity	10 - 85 %, non condensing
Dimensions (W x D x H)250 mm x 140 mm x 25 mmWeight1100 gNumber of Channels60, 120 or 256 channelsMeasurement range5 k0hm to 2 M0hmTest SignalsTest Signal100 mV, 1 kHz SinusAccuracy5 %Power SupplyPower supplyUSB poweredPC interfaceUSB 2.0	Storage Humidity	10 - 85 %, non condensing
Weight1100 gNumber of Channels60, 120 or 256 channelsNumber of channels60, 120 or 256 channelsMeasurement range5 kOhm to 2 MOhmTest SignalsTest signal100 mV, 1 kHz SinusAccuracy5 %Power SupplyUSB poweredPower supplyUSB poweredPof interfaceUSB 2.0	MEA-IT Device	
Number of Channels60, 120 or 256 channelsNumber of channels60, 120 or 256 channelsMeasurement range5 kOhm to 2 MOhmTest SignalsTest signal100 mV, 1 kHz SinusAccuracy5 %Power Supply5 %Power supplyUSB poweredPC interfaceUSB 2.0Software100 mV	Dimensions (W x D x H)	250 mm x 140 mm x 25 mm
Number of channels60, 120 or 256 channelsMeasurement range5 kOhm to 2 MOhmTest SignalsTest signal100 mV, 1 kHz SinusAccuracy5 %Power SupplyPower supplyUSB poweredPC interfaceUSB 2.0Software	Weight	1100 g
Measurement range     5 kOhm to 2 MOhm       Test Signals     100 mV, 1 kHz Sinus       Accuracy     5 %       Power Supply     5 %       Power supply     USB powered       PC interface     USB 2.0	Number of Channels	
Test Signals       Test signal       Accuracy       5 %       Power Supply       Power supply       USB powered       PC interface       USB 2.0	Number of channels	60, 120 or 256 channels
Test signal     100 mV, 1 kHz Sinus       Accuracy     5 %       Power Supply     5 %       Power supply     USB powered       PC interface     USB 2.0	Measurement range	5 kOhm to 2 MOhm
Accuracy     5 %       Power Supply     USB powered       PC interface     USB 2.0	Test Signals	
Power Supply     USB powered       PC interface     USB 2.0       Software     Image: Software	Test signal	100 mV, 1 kHz Sinus
Power supply     USB powered       PC interface     USB 2.0       Software     USB 2.0	Accuracy	5 %
PC interface USB 2.0 Software	Power Supply	
Software	Power supply	USB powered
	PC interface	USB 2.0
MEA-IT Control Version 1.5 and higher	Software	
	MEA-IT Control	Version 1.5 and higher
Operating system Microsoft Windows ® 10, (32 or 64 Bit), English and German versions suppor	Operating system	Microsoft Windows ® 10, (32 or 64 Bit), English and German versions supported

Phone +49-7121-909 25- 0 Fax +49-7121-909 25-11 sales@multichannelsystems.com www.multichannelsystems.com © 2022 Multi Channel Systems MCS GmbH a division of Harvard Bioscience, Inc.

Product information is subject to change without notice.